

# *Eagle* Concrete Polish

**PRODUCT DESCRIPTION:** Eagle CONCRETE POLISH is a water-based acrylic & wax co-polymer which forms a tough abrasion resistant clear non-yellowing top coat polish to protect existing sealers and finishes as finish on interior concrete floors. This co-polymer offers excellent gloss and can be stripped with conventional wax polish removers. Its toughness protects the existing finish and acts as a sacrificial coating for the hard sealed substrate. Eagle CONCRETE POLISH resists scuffs and marks while enhancing the gloss of the finish below. Eagle CONCRETE POLISH also increases slip resistance. It is designed to be applied on top of existing acrylic, polyurethane, and epoxy sealers. It is used on newly sealed floors and to restore shine on previously sealed concrete floors. Eagle CONCRETE POLISH is available in GLOSS and MATTE finishes in both one-gallon and five gallon containers.

**RECOMMENDED USES:** Eagle CONCRETE POLISH polishes Interior concrete floors only. It enhances decorative systems including stained concrete floors on both newly sealed floors and to regain the luster to worn areas of previously sealed and polished floors. Eagle CONCRETE POLISH may be used in homes, restaurants, stores, malls, office buildings, healthcare centers, hotels, motels, etc.

**PREPARATION:** Floor should clean, sealed and dry.

**APPLICATION:** Apply with lambs wool, sponge mop, or micro-fiber applicator. 2 or 3 initial coats is preferred. Allow 30 -60 minutes between coats to dry. Eagle CONCRETE POLISH can be buffed with high speed buffing machine but is not necessary Allow 4 hours to cure and dry before foot traffic resumes. Re-apply as needed. High traffic areas can be touched up as needed.

**Maintenance cleaning of the polished surface should be accomplished using ONLY water or Pledge Multi-surface cleaner and a soft mop. DO NOT USE aggressive cleaning agents, such as citrus-based, ammonia, or 409/Simple Green cleaners. Using an abrasive cleaning tool will scratch and dull the polished surface, requiring re-application of Eagle CONCRETE POLISH to restore the shine.**

**COVERAGE:** 1000 ft<sup>2</sup> per gallon per coat. 2-3 coats may be preferred.

**CLEAN UP:** Clean up with water immediately after use.

**DISCLAIMER:** Manufacturer warrants the product to be free from defects and will replace or refund the purchase price of said products proven defective. Since the manufacturer has no control over handling, use, or storage; no guarantee expressed or implied is offered. The suitability of the product for any use shall be solely up to the user. Manufacturer retains right to legal venue.

## **TECHNICAL DATA:**

<b>Solids:</b>	30%	<b>Density:</b>	8.5 lbs/gallon
<b>VOC:</b>	0.56lbs/gallon (67 g/l)	<b>pH:</b>	8.0-9.0
<b>Flash point:</b>	Non-combustible	<b>Freeze/Thaw:</b>	stable

**CONTENTS:** Proprietary acrylic polymer, waxes, water.

**HMIS / NFPA:** Health=0 Flammability=0 Reactivity=0 Special Notice=0

Made in USA by  
EAGLE IFP Company